

#### LIFE SAFETY LEGEND


- PATH OF EGRESS TRAVEL
- EMERGENCY LIGHT W/ BATT. BACKUP
- REMOTE EMERGENCY EGRESS LIGHT W/ BATT. BACKUP
- EMERGENCY LIGHT
- EXIT SIGN
- DIRECTIONAL EXIT SIGN

#### EGRESS PLAN

3/32" = 1'-0"



NO WORK TO BE DONE IN SHADED AREA



#### OVERALL FLOOR PLAN

1/8" = 1'-0"



#### ROOM FINISH SCHEDULE

#	Name	Floor Finish	Base Finish	Wall Finish	Ceiling Finish	Area	Comments
101	ENTRY	C. TILE	C. TILE	DRYWALL PAINTED	2'-0" x 2'-0" LAY-IN	551 SF	
102	OFFICE	CARPET	VINYL	DRYWALL PAINTED	2'-0" x 2'-0" LAY-IN	182 SF	
103	CLO.	CARPET	VINYL	DRYWALL PAINTED	2'-0" x 2'-0" LAY-IN	21 SF	
104	CHANGING ROOM	LVT	VINYL	DRYWALL PAINTED	2'-0" x 2'-0" LAY-IN	474 SF	
105	V.I.P.	LVT	VINYL	DRYWALL PAINTED	2'-0" x 2'-0" LAY-IN	795 SF	

5

#### DOOR SCHEDULE

MARK	HEIGHT	WIDT H	FIRE RATING	PANEL MATERIAL	FRAME MATERIAL	HARDWAR E SET	CARD ACCESS	GASKET	WEATHER PACKAGE	DOOR STOP	B.F. HARDWARE
102A	6'- 8"	3'- 0"		S.C. WOOD	H.M.	1				X	X
103A	6'- 8"	3'- 0"		S.C. WOOD	H.M.	2				X	X
104A	6'- 8"	3'- 0"		S.C. WOOD	H.M.	2				X	X
105A	6'- 8"	3'- 0"	3HR	S.C. WOOD	H.M.	2		X		X	X
105B	6'- 8"	6'- 0"		METAL	N/A	3					X
105C	6'- 8"	6'- 0"		METAL	N/A	3					X
105D	6'- 8"	6'- 0"		METAL	N/A	3					X
105E	6'- 8"	6'- 0"		METAL	N/A	3					X
105F	6'- 8"	6'- 0"		METAL	N/A	3					X
105G	6'- 8"	6'- 0"		METAL	H.M.	3					X
105H	6'- 8"	6'- 0"		METAL	N/A	3					X

Grand total: 11

#### INTERIOR FINISH NOTES

- FLUSH SOLID CORE DOORS SHALL BE PRE-FINISHED AS MANUFACTURED BY MOHAWK.
- METAL DOORS ( TO BE PAINTED ) DOORS SHALL BE 1-3/4" THICK, FORMED OF 20 GAUGE, COLD ROLLED, PRIME QUALITY STEEL EQUAL TO STEELCRAFT L-20 DOORS. FULL FLUSH PANEL.
- ALUMINUM ENTRANCE DOORS & FRAMED TO BE MANUFACTURED BY TUBELITE OR KAWNEER, COLOR: CLEAR ANODIZED
- METAL FRAMES ( TO BE PAINTED ) METAL DOOR FRAMES FOR 1-3/4" DOORS SHALL BE MADE OF 16 GAUGE COLD ROLLED PR M QUALITY STEEL EQUAL TO STEELCRAFT F-16 FLUSH FRAMES. SIZE AS SHOWN ON DRAW NGS.
- METAL DRYWALL FRAMES ( TO BE PAINTED ) METAL DOOR FRAMES FOR 1-3/4" DOORS SHALL BE FABRICATED FROM 16 GAUGE COLD ROLLED QUALITY STEEL EQUAL TO STEELCRAFT DW-16 DRYWALL FRAMES.
- HARDWARE:  
ALL HARDWARE SHALL BE YALE 5400LN SERIES PACIFIC BEACH BRUSHED ALUMINUM SURFACE  
ALL CLOSERS SHALL BE MANUFACTURED BY LCN CLOSERS, DIVISION OF SCHLAGE LOCK CO.  
WALL OR FLOOR BUMPERS SHALL BE INSTALLED AT EVERY DOOR AND SHALL BE AS MANUFACTURED BY RUSSWIN OR EQUAL.
- WALL BASE TO BE SOLID WOOD TO MATCH WALL F NISH
- PAINTING:  
SHERWIN WILLIAMS, PRIMER; "PREP-RITE" CLASSIC NTERIOR LATEX PRIMER WHITE  
GALVANIZED METAL: LATEX, SEMI-GLOSS, EGG SHELL, FLAT FINISH  
FERROUS METAL: LATEX, SEMI-GLOSS, EGG SHELL SATIN, FLAT FINISH  
GALVANIZED, CEILINGS, DUCTWORK: DRYFALL WATERBORNE SYSTEM, EGG SHELL FINISH  
DRYWALL: LATEX; SEMI-GLOSS, EGG SHELL, FLAT FINISH  
MASONRY: EPOXY; (WATER BASE) GLOSS FINISH  
WOOD, WALLS, CLGS, DOORS & TRIMS: LATEX; SEMI-GLOSS, EGG SHELL, FLAT FINISH
- CE LINGS:  
AS INDICATED ON REFLECTED CE LING PLAN
- SPECIAL ITEMS:  
RESTROOM COUNTER TOPS & BACKSPLASH: COLORS AS SPECIFIED. FURNITURE SHOWN W LL BE SPECIFIED BY OWNER
- PROVIDE CORNER GUARDS @ ALL 90 DEG CORNERS
- RESTROOM:  
HAND DRYER: XLERATOR, MODEL #XL-SB, BRUSHED STAINLESS STEEL COVER  
"BOBRICK" SOAP DISPENSERS B 8266, GRAB BARS,  
#B-380P, PROV DE DBL-ROLL SURFACE MOUNT PAPER DISPENSER #B-27480  
SURFACE MOUNT SANITARY WAPKIN DISPOSAL #B-270, ST STL GRAB BARS  
#B-490 SERIES BOBRICK FRAMELESS ST STL MIRROR #B-1556
- JANITOR ROOM: MOP HOLDERS: #B-224, PAIL HOOK: #B-220, HOSE HOLDER #B-640
- SIGNAGE: RAISED LETTER SIGNAGE WITH BRA LLE AT ENTRIES, RESTROOMS, JANITOR CLOSET, AND MECHANICAL ROOMS
- PROVIDE FIRE EXT NGUISHERS AND RECESS CABINETS AS REQUIRED.
- SEE PLUMB NG DRAWING FOR SPEC FIED FIXTURES.

#### HARDWARE SETS

SET #1	SET #2
1.5 EA. BALL BEARING SELF CLOSING H NGES	1.5 EA. BALL BEARING HINGES
1 EA. LOCKSET HARDWARE	1 EA. PASSAGE HARDWARE
1 EA. DOOR STOP	1 EA. DOOR STOP

SET #3
1 EA. PASSAGE HARDWARE
1EA. NON-BINDING TRACK


#### UL U426 DETAIL

##### INTERIOR PARTITIONS: STEEL STUD (LOAD-BEARING)

FIRE RATING: 3 HOUR  
STC: N/A  
SOUND TEST: N/A  
SYSTEM THICKNESS: 7-1/2"

##### GENERAL NOTES:

- SEE COMPLETE UL SPECIFICATION, SHEET A102
- BE SURE TO FOLLOW UL SCREW PATTERN SPECIFICATION
- CONTRACTOR TO FOLLOW INSPECTION PROTOCOL PER CITY REQUIREMENTS



##### ASSEMBLY OPTIONS:

GYPSUM BOARD: FOUR LAYERS OF 1/2 IN. THICK GYPSUM BOARD APPLIED HORIZONTALLY OR VERTICALLY.  
STEEL STUDS: 3-1/2 IN. DEEP, 20 GA. SPACED MAX. 24 IN. O.C.  
GYPSUM BOARD: FOUR LAYERS OF 1/2 IN. THICK GYPSUM BOARD APPLIED HORIZONTALLY OR VERTICALLY.

#### INTERIOR FINISH MATERIALS

ALL INTERIOR F NISHES ARE TO MEET CHAPTER 8 OF THE M.B.C. FINISH MATERIALS ARE TO BE CLASSIFIED IN ACCORDANCE WITH ASTM E 84 OR UL 723 AND ARE TO HOLD MATERIAL SMOKE DEVELOPMENT INDEXES AS SHOWN BELOW FOR EACH INTERIOR OCCUPIED SPACE:

NTERIOR EXIT STAIRWAYS, EXIT RAMPS, AND EXIT PASSAGEWAYS - **CLASS A**

CORRIDORS AND ENCLOSURE FOR EXIT ACCESS STAIRWAYS AND EXIT ACCESS RAMPS - **CLASS A**


ROOMS AND ENCLOSED SPACES - **CLASS B**

MATERIAL SMOKE DEVELOPMENT INDEXES:

**CLASS A:** = FLAME SPREAD INDEX: 0-25  
SMOKE DEVELOPMENT NDEX: 0-450

**CLASS B:** = FLAME SPREAD INDEX: 26-75  
SMOKE DEVELOPMENT NDEX: 0-450

**CLASS C:** = FLAME SPREAD INDEX: 76-200  
SMOKE DEVELOPMENT NDEX: 0-450




#### KEY PLAN

1" = 30'-0"









3  
A102/A102 3/4" = 1'-0"

UL #426 FIRE BARRIER WALL SECTION




2  
A102/A102 3/4" = 1'-0"

TYP. WALL SECTION



4  
A102/A102 3/4" = 1'-0"

TYP. VIP WALL SECTION



1  
A101/A102 1/4" = 1'-0"

ENLARGED FLOOR PLAN

NORTH

### ELECTRICAL LEGEND

- 2x4 LAY-IN LIGHT (EXISTING)
- RECESSED LIGHT FIXTURE
- WALL RECEPTACLE
- DATA
- SINGLE POLE SWITCH